

THIS IS A SAMPLE OF THE TYPE AND SIZE OF THE FIRE EXTINGUISHERS REQUIRED AS PART OF THE CERTIFICATE OF COMPLIANCE FOR RESIDENTIAL REALES. THIS IS ONE EXAMPLE OF FIRE EXTINGUISHER MANUFACTURER, THEIR ARE OTHER MANUFACTURERS THAT MEET THIS SAME RATING. THE MANUFACTURER IS YOUR CHOICE.

Pro 210 Consumer Fire Extinguisher

Part number 21005779

Multipurpose use

Rechargeable

UL Rated 2-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).


The PRO 210 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a tough aluminum valve assembly.

Features bilingual nameplate and carton.

Features

- Multipurpose Fire Extinguisher
- Aluminum cylinder
- Tough aluminum valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable unit.
- Assembled in Mexico from global components.
- 6 year warranty
- UL rated 2-A, 10-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Optional metal strap bracket Pt # 466400
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



FOR LOW HAZARDS

A 2-A:10-B:C rated extinguisher is required for protecting LOW hazard occupancies such as:
living areas of the home, offices, churches, assembly halls, classrooms & hotel guest areas.



Pt # 21005779 - 4 pack
UPC: 0-47871-05779-5
I2F - 10047871057792
Pt # 21007158 - 24 pack Lowe's
UPC: 0-47871-05779-5
I2F - 20047871057799

Product Specification

Net agent weight (Average)	4 lb.
Unit weight (Average)	7.5 lb.
Diameter	4.5 inches
Height	15.7 inches
Discharge time	13-15 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve/handle/lever	Aluminum
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



MASTER PACK

Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	16.0
Master Pack	13.0	17.25	9.87

Residential Series

Living Area Fire Extinguisher (Primary Protection)

Part number 21005770

Living area use

Single use

UL Rated 2-A:10-B:C



Meets NFPA recommendations for primary home protection



Description

Fights fires common to the home living areas such as wood, fabrics, furnishings, and drapes.

Meets NFPA recommendations for primary home protection and has a 10 year warranty.

Features bilingual nameplate and carton.

White finish.

Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 4 lb. of fire extinguishing agent (Average)
- 10 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection



UPC: 0-47871-05770-2

For use on the following types of fire:



At a Glance


- Model FX210R
- Multipurpose Dry Chemical
- UL listed
- UL rated 2-A:10-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 10 year limited warranty

Product Specification

Net agent weight (Average)	4.0 lb.
Unit weight (Average)	7.13 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Wall hanger	UL Listed

Packaging Options

Master Pack (2)	21005770
Master Pack (4)	21005771
Cut Case (8)	21005772



MASTER PACK



MASTER PACK



CUT CASE